

MOD. TL-PSG-E



Mod.	TL-PSG-E	PSG-E30	PSG-E40	PSG-E60	PSG-E80	PSG-E120	PSG-E150
Potenza di targa(w)		30	40	60	80	120	150
Flusso luminoso lm		4470	7152	8940	11920	17880	22350
Peso (kg)		5	5,5	6	6	6,5	6,5
Dim L x H x P (mm)		850,00 x 215,00					
Installazione tipica		A Palo/Braccio					
Materiale corpo lam		Alluminio - Aluminium 6060T5					
Colore corpo lamp		Anodizzato nero - Anodized black					
Schermo lampada		Vetro temperato - Tempered glass					
Temp. Di colore(k)		3000°k/4000°k/5000°k					
Indic. Di resa (CRI)		CRI ≥ 90					
Durata utile		> 60.000 ore / hours					
Fattore di Potenza		> 0,95					
Classe di isolament		IP66					
Temp. Operativa		-30 C° / + 60° C					
Risch. Fotobiologico		Direttiva 2006/25/CE IEC/EN62471					
Classe Energetica		A+					
Tensione Aliment.		100-240 Vac -50/60 Hz					

Dati riferiti a lampada con LED a 5.000K° - Data refers to lamp with LED at 6.500K

Caratteristiche soggette a cambiamenti e miglioramenti senza preavviso

LED OSRAM



Produzione e progettazione e Vendita Lampade Led